

Ash & Lacy Building Systems Limited

Bromford Lane
West Bromwich
West Midlands
B70 7JJ

Tel: 0121 525 1444
Fax: 0121 525 3444
Web: www.ashandlacy.com




Product Datasheet – Masonry Fixings

Carbon steel self-tapping

Application:	General purpose masonry fixings
Head Options:	5/16"(8mm) A/F Hex and Countersunk Head
Washer Options:	16mm, 19mm galvanised steel / EPDM vulcanised
Material:	Carbon steel
Coating:	Blue organic finish provides lower overall tapping torque and excellent corrosion resistance

Hexagon head to concrete or masonry			
Product Code	Diameter x Length (mm)	Fixture Build-up range (mm)	
		Minimum	Maximum
MF32	6.3 x 32	0	7
MF45*	6.3 x 45	5	20
MF57	6.3 x 57	17	32
MF70	6.3 x 70	30	45
MF82	6.3 x 82	42	57
MF100	6.3 x 100	60	75
MF125	6.3 x 125	85	100



* This size is also available on Stainless Steel

Countersunk head to concrete or masonry			
Product Code	Diameter x Length (mm)	Fixture Build-up range (mm)	
		Minimum	Maximum
MF45C	6.3 x 45	5	20
MF57C	6.3 x 57	17	32
MF70C	6.3 x 70	30	45
MF82C	6.3 x 82	42	57
MF100C	6.3 x 100	60	75
MF125C	6.3 x 125	85	100



Drill Bit			
Product Code	Diameter x Length (mm)	Masonry Fixing Range (mm)	
		Minimum	Maximum
MF-DR140	5.15 x 140	32	100

Notes:

Minimum embedment for concrete is 25mm
Minimum embedment for brick/blockwork is 35mm
Drill hole depth should be minimum of 10mm more than the embedment depth
Performance is dependant on concrete/masonry material and condition
Site testing is recommended. For further information please contact the technical department