

TECHNICAL DATA SHEET

ELASTO-THANE CATALYST ACCELERATING ADDITIVE

Issue 1- Sep 2014

DESCRIPTION:

The ELASTO-THANE CATALYST is an accelerating additive for use with the ELASTO-THANE liquid-applied polyurethane waterproofing membranes.

USES:

The ELASTO-THANE CATALYST is mainly used when the ELASTO-THANE, needs to be applied in very low temperatures or when the ELASTO-THANE, needs to be applied in combination with the GLASS FIBRE SCRIM in the wet-in-wet application method (higher coating thicknesses in one layer)

APPLICATION:

Stir the ELASTO-THANE well, before using. Add the correct quantity of ELASTO-THANE CATALYST and mix by low speed mechanical stirrer, for about 3-5 min.

ATTENTION: The mixing of the components has to be effected very thoroughly, especially on the walls and bottom of the pail until the mixture becomes fully homogeneous.

After the mixing, pour the mixture onto the prepared surface to be waterproofed, and spread it out. All application instructions and/or techniques of the ELASTO-THANE need to be observed and followed. Make sure to use the ELASTO-THANE +ELASTO-THANE CATALYST mixture, within the stipulated Pot Life.

Dosage:

ELASTO-THANE : ELASTO-THANE CATALYST = 100 : 3 or 25kg : 0.75kg

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com