

Deepstyle 170

170mm Industrial Rainwater System







Deepstyle 170

170mm Industrial Rainwater System

Brett Martin's Deepstyle 170 is a high performance industrial rainwater system offering increased drainage capacity for larger commercial projects, factories, warehouses, farm buildings and apartments. The design features innovative CLIP & SEAL technology for ease of installation, superior sealing and exceptional reliability.

Strong and durable, Deepstyle 170 is a heavy duty gutter system, manufactured from UV resistant PVC. The system's robustness has been fully tested to BS EN 1462 Load Class H, whilst its unique formulation provides long-term weatherability for the systems high gloss gutter, fittings and downpipes, which are covered by a 10 year colour warranty.



I I 0mm INDUSTRIAL DOWNPIPE

Deepstyle 170 integrates seamlessly with Brett Martin's 110mm Industrial Downpipe System completing the high capacity offer. Comprising 110mm plain ended or single socket downpipe options, with high quality PVCu fittings, including bends, branches, access pipes and clips, the system retains the adaptability essential in planning an industrial rainwater scheme.

At ground level, the rainwater system is fully compatible with Brett Martin's extensive underground drainage systems.





UNION BRACKET – BR094



Deepstyle 170

EXTERNAL STOPEND – BR097

Plumbing & Drainage 170mm Industrial Rainwater System



GUTTER – BR091/92

HIGH CAPACITY 170mm elliptical gutter profile



DEEPSTYLE 170 AT A GLANCE

- 170mm high performance industrial rainwater system with a greater drainage capacity
- This large scale system enables larger roofs to be drained more efficiently and effectively
- All fittings feature factory fitted CLIP & SEAL technology for ease of installation and completely watertight joints
- The system requires fewer downpipes and drainage connections
- High gloss UV protected gutter and downpipes which look better and last longer

DEEPSTYLE 170 FOR LARGER ROOFS

- Commercial: schools, hospitals, offices
- Industrial: factories, warehouses
- Agricultural: barns, cow sheds, outbuildings
- Residential: apartments, barn conversions, large period properties and residences

Colour Options





ACK GREY

DEEPSTYLE 170 INDUSTRIAL RAINWATER SYSTEM

| | GUTTER FLOW CAPACITY LITRES PER SECOND | MAXIMUM ROOF AREA m ² |
|-------------------|---|-------------------------------------|
| | 1:600 | 1:600 |
| Outlet at one end | 5.12 | 244 |
| Outlet at centre | 10.24 | 488 |
| | 1:350 | 1:350 |
| Outlet at one end | 5.77 | 275 |
| Outlet at centre | 11.54 | 550 |

^{*}Actual test results calculated in site conditions

CLIP & SEAL

- Brett Martin's Deepstyle 170 rainwater system features a new and innovative factory fitted CLIP & SEAL to ease the installation process and provide exceptional long-term sealing reliability.
- The unique CLIP & SEAL fully integrates with the fitting so that the specially designed captive seal is held securely within the fitting whilst the clip locks the seal firmly in place.
- For added convenience the CLIP & SEAL is fully factory fitted to all Deeptyle 170 fittings but can also be easily removed if required.
- When fitting the gutter the CLIP & SEAL provides just enough flex to allow the gutter to locate within the fitting, whilst a reassuring click locks the gutter securely into position compressing the seal for superior sealing.



Deepstyle 170 Range

| 170mm INDUSTRIAL RAINWATER SYSTEM | | | | | | | |
|-----------------------------------|-------|--|--------|----------|--|--|--|
| | CODE | DESCRIPTION | COLOUR | PACK QTY | | | |
| GUTTERS | | | | | | | |
| | BR091 | 2m Gutter | B G | 4 | | | |
| | BR092 | 4m Gutter | B G | 4 | | | |
| BRACKETS | I | | | | | | |
| c R will | BR093 | Multi Fix Fascia Bracket | B G | 10 | | | |
| | BR094 | Union Bracket | B G | 4 | | | |
| OUTLET & STOPENDS | | | | | | | |
| | BR095 | Running Outlet | B G | 2 | | | |
| | BR096 | Internal Stopend | B G | 10 | | | |
| | BR097 | External Stopend | B G | 10 | | | |
| GUTTER ANGLES | | | | | | | |
| The state of | BR098 | Gutter Angle 90° | B G | 2 | | | |
| | BR9 | Non-Standard Angles (Available on Request) | ВG | I | | | |
| RISE & FALL BRACKET | | | | | | | |
| | BRF9 | Rise & Fall Bracket | Galv | I | | | |



Plumbing & Drainage

| | | | CODE | DESCRIPTION | COLOUR | PACK QTY |
|--------------|----------------|-------|-------|--|---------|----------|
| PIPES, PLAIN | N ENDED | | | | | |
| ==, : = : | | | BS402 | 2.5m Pipe | BG | 2 |
| | | | BS403 | 3m Pipe | BW G Br | 2 |
| | | | BS404 | 4m Pipe | BW G Br | 2 |
| DIDEC CIVIC | LECOCKET | | BS405 | 6m Pipe | B G | 2 |
| PIPES, SIING | LE SOCKET | | BS413 | 2.5m Pipe | B G Br | 2 |
| | -6110 | | BS414 | 3m Pipe | BW G Br | 2 |
| | | | BS415 | 4m Pipe | B G Br | 2 |
| | | | BS430 | 6m Pipe | B G | 2 |
| CONNECT | ORS & COUPLI | ING | | | | |
| _ | _ | | BS406 | Double Socket Pipe Connector | BW G Br | 20 |
| 2 1 | | | BS432 | Single Socket Pipe Connector | B G Br | 20 |
| | | | BS478 | Double Socket Clip Connector | BG | 10 |
| S406 BS | S432 BS478 | BS433 | BS433 | I I 0mm to I 49mm A.C. Gutter Outlet | BG | 10 |
| BRACKETS | | | | | | |
| | | | BS407 | Double Fixing Pipe Bracket | BW G Br | 10 |
| | | | BS438 | Single Fixing Pipe Bracket | ВG | 10 |
| BS407 | BS438 | BS450 | BR450 | Metal Pipe Bracket | Galv | 5 |
| SINGLE SO | CKET BENDS | | | | | |
| | - | | BS408 | 112½° Single Socket Offset Bend | BW G Br | 10 |
| | | | BS409 | 112½°Single Solvent Weld Socket Bottom Offset Bend | BW G Br | 10 |
| | | | BS420 | 92½° Single Socket Bend | BW G Br | 10 |
| BS408 | BS409 | BS420 | BS421 | 112½° Single Socket Bend | B G Br | 10 |
| | | | BS422 | 135° Single Socket Bend | B G Br | 15 |
| | | | | | | |
| 1 | | | BS436 | 92½° Single Socket Access Bend | B G | I |
| | BS422 BS436 | BS424 | BS424 | 0°-30° Adjustable Single Socket Bend | G | 5 |
| DOUBLE SC | OCKET BENDS | | | | | |
| | | | BS480 | 92½° Double Socket Bend | BG | 10 |
| | | · | BS482 | 135° Double Socket Bend | B G | 15 |
| BS48 | _ | BS482 | D3702 | 133 Double socket Belld | ВО | 15 |
| SHOE, HEA | D & ACCESS PIF | PE | | | | |
| | | | BS416 | I 12½° Downpipe Shoe | B G Br | 15 |
| 1 | | | BS411 | Rainwater Head | B G Br | I |
| BS416 | BS411 | BS410 | BS410 | Single Socket Access Pipe | B G Br | I |
| BRANCHES | S | | | | | |
| | n Ma | | BS417 | 92½° Double Socket Branch without Bosses | ВG | 7 |
| | | | BS457 | 92½° Triple Socket Branch without Bosses | ВG | 7 |
| T 1 | | | BS419 | 135° Double Socket Branch without Bosses | ВG | 5 |
| BS417 BS4 | 457 BS419 | BS447 | BS447 | 92½° Double Socket Access Branch | ВG | I |
| DRAIN CO | NNECTOR | | | | | |
| | | | BS423 | 110mm Pipe to 160mm Drain Connector | B G Br | 15 |
| | | | D3423 | Tronini ripe to routiin Drain Connector | D D Df | 15 |
| | 1 | - 61 | BS434 | PVCu to Cast Iron & Salt Glaze Drain Connector | B G Br | 20 |



Plumbing & Drainage

Distributed by:

Brett Martin Daylight Systems Ltd Sandford Close, Aldermans Green Industrial Estate, Coventry, West Midlands CV2 2QU Tel: +44 (0) 24 7660 2022

Fax: +44 (0) 24 7660 2745 Email: daylight@brettmartin.com

For the latest company information visit the company's website: www.brettmartin.com







All reasonable care has been taken in the compilation of the information contained within this literature. All recommendations on the use of our products are made without guarantee as conditions of use are beyond the control of Brett Martin. It is the customer's responsibility to ensure that the product is fit for its intended purpose and that the actual conditions of use are suitable. Brett Martin pursues a policy of continuous product development and reserves the right to amend specifications without prior notice. StormCrate is a registered trademark of Brett Martin Ltd. StormCrate Stormwater Attenuation and Infiltration Crates are sold and supplied with the agreement of the manufacturer, Graf UK Ltd, Target House, Thorpe Way, Banbury, Oxfordshire OX16 4SP. Brett Martin Ltd.'s Normal Conditions of Sale apply.