

Metrotile Bond



Metrotile Bond: the classic pantile design that put Metrotile on the map.

This range is available in a choice of standard colours to suit particular design and planning requirements, however with additional lead time we can provide you with any colour you require for your project. For more details about this you can contact us.

Bond is available in two thicknesses, .410mm and .900mm with the latter being suitable for areas where vandalism is a concern in addition to extra resistance to rooftop foot traffic. Metrotile .410 profiles are suitable for the majority of standard rooftop applications.

Each tile is the equivalent of eight conventional roof tiles and may be fixed from vertical right down to a 10° pitch; tiles are overlapped and then fixed, providing excellent strength and durability.


LIGHTWEIGHT HIGH GRADE STEEL WITH ZAM COATING FOR INCREDIBLE STRENGTH AND RESISTANCE




AVAILABLE THICKNESS
.410mm and .900mm
suitable for most roofing applications

DESIGNED TO BE SUITABLE FOR PITCHES AS LOW AS

10°



BURNT UMBER



BRONZE




CHARCOAL



RED



GREEN



TERRACOTTA

BESPOKE COLOUR OPTIONS AVAILABLE BY REQUEST

Fixings & Battens

Tile Fixing:	50 x 2.5mm Coated Nail
Coated Nail:	Hand nailing or power tool
Fixings per tile:	4
Battens Required	5 linear metres per m ² (plus wastage)

Rafter Centres	Batten Size
450mm	25 x 50mm
600mm	25 x 50mm
900mm	50 x 50mm
1200mm	50 x 50mm
1500mm	50 x 65mm

Dimensions

Pitch:	Minimum: 10° / Maximum: 90°
Overall Size:	1330mm x 370mm
Cover Size:	1257mm x 370mm
Gauge:	.410mm/.900mm
Linear Cover Width:	1257mm
Coverage:	0.46 m ² / 2.15 per m ²
Weight per m ² :	6.2kg/9.9kg
Weight per tile:	2.8kg/4.6Kg



ISO9001
 ISO14001

